




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : <b>F02M 25/022</b>	<b>A1</b>	(11) International Publication Number: <b>WO 98/07975</b> (43) International Publication Date: 26 February 1998 (26.02.98)
<p>(21) International Application Number: PCT/SE97/01377</p> <p>(22) International Filing Date: 21 August 1997 (21.08.97)</p> <p>(30) Priority Data: 9603033-3 21 August 1996 (21.08.96) SE</p> <p>(71) Applicant (for all designated States except US): ABB POWERMAN AB [SE/SE]; Dunderbacksvägen 14, S-612 46 Finspång (SE).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): HANSSON, Hans-Erik [SE/SE]; Dunderbacksvägen 14, S-612 46 Finspång (SE).</p> <p>(74) Agents: NILSSON, Karl et al.; Stenhagen Patentbyrå AB, P.O. Box 4630, S-116 91 Stockholm (SE).</p>		<p>(81) Designated States: JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p><b>Published</b> With international search report. In English translation (filed in Swedish).</p>
<p>(54) Title: A METHOD OF OPERATING AN INTERNAL COMBUSTION ENGINE ARRANGEMENT AND SUCH AN ARRANGEMENT</p> <p>(57) Abstract</p> <p>In the operation of an internal combustion engine arrangement that includes at least one piston engine (1) having at least one combustion chamber, and means (2, 3, 4) for delivering fuel, air and water to the combustion chamber or to each combustion chamber, water vapour present in the engine exhaust gases is condensed by cooling the gases. The water of condensation is returned to the combustion chamber or to each combustion chamber. The arrangement includes to this end cooling means (11) for condensing water vapour in the engine exhaust gases and also means (15, 18, 19, 4) for feeding the condensation water to the combustion chamber or to each combustion chamber.</p> 		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

A METHOD OF OPERATING AN INTERNAL COMBUSTION ENGINE  
ARRANGEMENT AND SUCH AN ARRANGEMENT

5 The present invention relates to a novel method of operating  
an internal combustion engine arrangement that includes at  
least one piston engine having at least one combustion  
chamber, and means for delivering fuel, air and water to said  
combustion chamber or to each combustion chamber. The  
invention also relates to a combustion engine arrangement  
10 that works in accordance with the novel method.

It is known that important advantages can be achieved by  
supplying internal combustion engines with water. These  
advantages include an increase in efficiency and possible  
15 power output, low emission, particularly low NO<sub>x</sub> emissions,  
and low knocking tendencies. Methods and engines of the kind  
addressed by the present invention that operate with water-  
injection require large quantities of water. In order to  
avoid the risk of harmful water-carried salts precipitating  
20 out in the engines, the water used will preferably be clean  
water.

The object of the present invention is to provide a method  
and an arrangement in which the aforesaid drawbacks are  
25 eliminated at least to a substantial extent.

Accordingly, there is proposed to this end in accordance with  
the invention a method of the kind defined in the  
introduction in which the exhaust gases are cooled so as to  
30 at least partially condense the water vapour present in said  
exhaust gases and the water thus formed returned to the  
combustion chamber or to each combustion chamber, optionally  
after vaporising said water. Condensation of the water vapour  
and recycling of said water beneficially reduces, or  
35 eliminates, the need to supply fresh water.

In accordance with the present invention, an internal combustion engine arrangement that includes at least one piston engine having at least one combustion chamber, and means for delivering fuel, air and water to the combustion chamber, or to each combustion chamber, includes cooling means for condensing water vapour contained in the engine exhaust gases, and means for returning the water of condensation to the combustion chamber, or to each combustion chamber.

Other features characteristic of the invention are set forth in the accompanying dependent Claims and are also made apparent in the following description of exemplifying embodiments of the inventive arrangement shown in the accompanying, schematic drawings, in which

Fig. 1 illustrates schematically a first embodiment of the inventive arrangement; and

Fig. 2 illustrates schematically a second embodiment of the inventive arrangement.

Those components and features illustrated in the Figures that finding mutual correspondence, or generally mutual correspondence, have been identified with the same reference signs.

Fig. 1 illustrates an internal combustion engine arrangement that includes an internal combustion piston-engine 1. Fuel, air and water are delivered to the engine 1 through respective conduits 2, 3 and 4. The water supplied may have been converted to vapour form by means not shown, prior to being delivered to the engine. The engine exhaust gases depart through the conduit 5. The internal combustion engine arrangement may be a stationary arrangement used to run an electric generator and the heat generated used for heating

purposes, for instance. However, the arrangement can also be used with automotive vehicles, for instance. The engine exhaust gases are used to operate a supercharger that includes an exhaust gas turbo 6 which drives , via a shaft 7, a compressor 8 in which the air of combustion is compressed prior to delivery of the air to the engine and to which air arrives via an air filter 9. In the case of Otto engines, air and fuel may be mixed together prior to being delivered to the engine 1, and the air/fuel mixture can be compressed in the supercharger 6, 7, 8 prior to delivery of the mixture to the engine. This procedure is appropriate when using gaseous fuel, such as natural gas, generator gas, landfill gas, etc.

The exhaust gases are delivered from the exhaust turbo 6, either before or after being cleaned, through a conduit 10 to a cooler 11, in which the exhaust gases are cooled to condense a substantial part of their water vapour content. The remainder of the exhaust gases depart through the conduit 12, whereas the water of condensation is delivered through a conduit 13 to a water tank 15, optionally via a filter 14 for extracting water-carried solids. The level of water in the tank 15 is referenced 16 and, as indicated by the arrow 17, the tank 15 may be provided with means for maintaining a determined level of water therein. Water is pumped from the tank 15 to the engine 1 by means of a pump 18, via a conduit 19 and the conduit 4. Water can be pumped via a conduit 20 branching from the conduit 19 to the cooler 11 where the water can be injected directly into the exhaust gases and therewith cool said gases and promote condensation of the water vapour in the exhaust gases and rinse clean the heat-exchange surfaces in the cooler. The water arriving through the conduit 20 and injected into the cooler 11 accompanies the condensate formed in the cooler through the conduit 13 and back to the tank 15. The flow of water in the conduits 4, 19, 20 is controllable, e.g. by means of a valve arrangement not shown.

When operating the internal combustion engine arrangement shown in Fig. 1, the water tank 15 is conveniently filled initially with water to the desired level and the engine 1 then started. It will be realised, however, that as the fuel is combusted in the engine, it will give rise to water vapour that is condensed in the cooler 11, wherewith the condensate thus formed is collected in the tank 15. The exhaust gases may advantageously be cooled in the cooler 11 to such an extent as to obtain sufficient condensate to render the arrangement self-supporting with respect to its water requirement in continuous operation, so as to obviate the need to supply the arrangement with fresh water after possibly filling the tank 15 initially to the level desired. When fresh water is supplied to the arrangement, any salts dissolved in the water are liable to precipitate into the engine. The amount of water delivered to the engine 1 through the conduit 4 may be chosen in dependence on the result desired, but will advantageously be adapted so that said amount will at least correspond to the amount of fuel delivered to the arrangement, and preferably from one to five times as much. When operating an internal combustion engine arrangement fuelled with natural gas, in which water and fuel were delivered to the engine in identical quantities, it was found that equilibrium was reached, i.e. the arrangement became self-supporting with respect to water, when the engine exhaust gases were cooled to about 58°C.

The invention comes particularly into its own when the engine concerned is an Otto engine. In this case, air and fuel can be delivered in stoichiometric ratios, whereby very effective exhaust gas purification can be achieved with the aid of a so-called three-path catalyzer. The water supplied to the engine arrangement effectively avoids the typical knocking tendency of the Otto engine and the otherwise high temperature generated in stoichiometric combustion, so as to

make overcharging to high pressures possible. This results in greater efficiency and enables the power output of a given engine to be increased. The injection of water results in lower emissions, particularly lower NO<sub>x</sub> emissions, 5 irrespective of the type of piston engine concerned, and also a cooling effect that affords higher compression ratios and therewith greater efficiency.

When the exhaust gases are cooled to a temperature of about 10 55-60°C for instance, the coolant used in the cooler 11 is heated to a relatively low temperature of e.g. about 50-60°C, even when using counterflow cooling in the illustrated manner, which may limit the usefulness of the thermal energy recovered in the cooler. Thermal energy of greater quality 15 can be recovered from the engine exhaust gases, which normally have a temperature in the order of 600-650°C, when the exhaust gases are cooled in more than one stage. In this case, the engine exhaust gases are cooled in a separate, first stage to a temperature that lies above the dew point of 20 the water vapour present in these engine exhaust gases, and then cooled in at least one following stage to condense a desired quantity of water vapour therefrom.

Fig. 2 illustrates a two-stage cooling process in accordance 25 with the above. The internal combustion engine arrangement shown in Fig. 2 is essentially the same as that described with reference to Fig. 1 in other respects and only those parts of the arrangement that differ from the arrangement shown in Fig. 1 will be described. Thus, the Fig. 2 30 arrangement includes two mutually sequential exhaust gas coolers 21, 22. The engine exhaust gases are delivered to the first cooler 21 at a relatively high temperature, e.g. a temperature of about 600°C, optionally after having first been cleaned. The exhaust gases are cooled indirectly in the 35 cooler 21 to a temperature above the dew point of the water

vapour present in the exhaust gases while recovering high-quality heat therefrom. The exhaust gases are finally cooled in the following cooler 22 while condensing the water vapour present in said gases, partly by heat exchange and partly by  
5 injecting water through the conduit 20 in an amount controlled by means of a valve 23. The remainder of the exhaust gases depart from the cooler 22 at 12.

10 It will be understood that the invention is not restricted to the aforescribed and illustrated exemplifying embodiments thereof and that the invention can be implemented in any suitable manner within the scope of the inventive concept defined in the following Claims.



## CLAIMS

1. A method of operating an internal combustion engine arrangement that includes at least one piston engine (1) having at least one combustion chamber, and also means (2, 3, 4) for delivering fuel, air and water to the combustion chamber or to each combustion chamber, characterized by cooling the exhaust gases such that at least part of the water vapour present in the engine exhaust gases will be condensed, and returning the water of condensation thus formed to the combustion chamber or to each combustion chamber, optionally subsequent to vaporising said condensation water.
2. A method according to Claim 1, characterized by delivering at least as much water as fuel, suitably from one to five times as much water.
3. A method according to Claim 1 or Claim 2, characterized by first cooling the engine exhaust gases in a separate stage (21) to a temperature that lies above the dew point of the water vapour present in the engine exhaust gases.
4. A method according to any one of Claims 1-3, characterized by cooling the exhaust gases by injecting water therinto, suitably condensation water obtained from said exhaust gases.
5. A method according to any one of Claims 1-4, characterized in that the piston engine, or each piston engine (1), is an Otto cycle engine to which fuel and air are delivered in at least substantially stoichiometric ratios.
6. An internal combustion engine arrangement that includes at least one piston engine (1) having at least one combustion chamber, and means (2, 3, 4) for delivering fuel, air and

5 water to the combustion chamber or to each combustion chamber, **characterized** by cooling means (11; 21, 22) for condensing water vapour from the engine exhaust gases, and means (15, 18, 19, 4) for returning the water of condensation to the combustion chamber or to each combustion chamber.

10 7. An arrangement according to Claim 6, **characterized** by a condensate collecting vessel (15) which is connected downstream of said cooling means (11; 21, 22) and from which condensation water is cycled back to the combustion chamber or to each combustion chamber.

15 8. An arrangement according to Claim 6 or 7, **characterized** in that said cooling means (11; 21, 22) includes at least one cooler (11; 22) through which the exhaust gases flow, and which uses water injected therein as a coolant.

20 9. An arrangement according to Claim 8, **characterized** in that said cooling means (21, 22) includes a first cooler (21) in which indirect heat exchange is effected between the engine exhaust gases and the coolant, such as to cool the gases to a temperature above their dew point, and a second, following cooler (22) in which water vapour present in the exhaust gases is condensed, said second cooler preferably  
25 operating with direct injection of coolant into the exhaust gases.

30 10. An arrangement according to any one of Claims 6-9, **characterized** in that the piston engine or each piston engine (1) is an Otto cycle engine that operates with an at least substantially stoichiometrical fuel/air ratio.




Fig. 1




Fig. 2

1  
INTERNATIONAL SEARCH REPORT

International application No.  
PCT/SE 97/01377

**A. CLASSIFICATION OF SUBJECT MATTER**

IPC6: F02M 25/022

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC6: F02M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4611557 A (HIERZENBERGER), 16 Sept 1986 (16.09.86), abstract --	1,2,5-7,10
X	EP 0305351 A2 (TIBERG, LARS), 1 March 1989 (01.03.89), abstract	1-3,5,6,9,10
Y	--	4,7,8
X,P	WO 9714884 A1 (ERDGAS ENERGIE SYSTEME GMBH ET AL), 24 April 1997 (24.04.97), abstract --	1-10
Y	US 3696795 A (SMITH ET AL), 10 October 1972 (10.10.72), column 9, line 55 - line 64 --	4,7,8

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

14 November 1997

1997 -11- 24

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Dan Ionesco  
Telephone No. +46 8 782 25 00

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

01/10/97

International Application No.  
PCT/SE 97/01377

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4611557 A	16/09/86	CS 269973 B CS 8506906 A DE 3560845 A EP 0177484 A,B SE 0177484 T3 JP 61085565 A	14/05/90 13/10/89 03/12/87 09/04/86  01/05/86
EP 0305351 A2	01/03/89	DK 473388 D SE 458800 B SE 8703338 A US 4918916 A US 4945829 A	00/00/00 08/05/89 01/03/89 24/04/90 07/08/90
WO 9714884 A1	24/04/97	DE 19538067 A	17/04/97
US 3696795 A	10/10/72	NONE	

**THIS PAGE BLANK (USPTO)**